

iPrism® h-Series Appliances

iPrism's new line of high-performance hardware offers a full range of appliances designed to deliver maximum performance and throughput speeds with a range of models to accommodate any size organization.

The iPrism h-Series high performance appliances offer a completely self-contained solution with its own hardened and optimized OS. With throughput speeds of 10 to 100+ Mbps, you are assured unrivalled performance no matter how large a pipeline your organization supports. The compact, 1U, h-Series appliances are compatible with all supported versions of iPrism software.

Speak with an iPrism representative today to choose the h-Series appliance that best fits your requirements.



- Optimum Power
- Fast Throughputs from 10 to 100 Mbps!

Model:	10h	20h	30h	50h	100h
Form Factor	Mini-1U Rack-Mountable		1U height, rack-mountable		
Dimensions	1.75"(H) x 14"(W) x 16.7"(D)		1.75"(H) x 14"(W) x 25.6"(D)		
Weight	15 lbs		50 lbs		
Rails	Included				
Chipset	Intel 946GZ+ICH7R+Intel 82573		Intel 5000P		
Processor	Intel Pentium 4 Processor	Intel Core 2 Duo 2.13 GHz	Intel Dual-Core Xeon 1.6 GHz	Intel Quad-Core Xeon 2.0 GHz	Dual Intel Quad-Core 3.0 GHz
Disk	1 x 80 GB SATA		2 x 250 GB Hot Swap SATA		2 x 500 GB Hot Swap SATA
RAID Controller	N/A		3ware 9500-2LP, RAID controller, RAID 1 (Mirrored)		
Memory	1024MB (1GB) RAM (DDR2 533)		1024MB (1GB) SDRAM (DDR2 Registered ECC Server RAM)	2048MB (2GB) SDRAM (DDR2 Registered ECC Server RAM)	4096MB (4GB) SDRAM (DDR2 Registered ECC Server RAM)
Ethernet interfaces	2 x 10/100/1000				
Network Failover Circuit	N/A	Management NIC, 2 x 10/100/1000, Full Duplex Interfaces, with BYPASS circuit			
AC Power	115-230 VAC, 50-60 Hz, 4.0A@115V; 200W		100-240 VAC, 50-60 Hz, 4.0-8.0A@115V; 650W		
Dual Hot-Swap Power Heat	N/A		Yes		
Heat	1320 BTU per hour (max.)		1850 BTU per hour (max.)		
Operating Temperature	10 to 35°C, 50 to 95°F				
Throughput	10 Mbps	20 Mbps	30 Mbps	50 Mbps	100+ Mbps

Corporate Office – USA

15015 Avenue of Science, San Diego, California 92128, USA

Phone : (858) 676-2277

Fax: (858) 676-2299

Toll-Free: (800) 782-3762

Email: info@stbernard.com

